



## PRODUCTS

Core Automation Incorporated's fully-equipped manufacturing facility is qualified and capable of fabricating, assembling, wiring and testing electrical and control systems equipment. Core Automation, Inc. provides fabrication and design services for most hardware and software vendors, which allows us to integrate and support a full complement of hardware and software solutions for *your* control system. If you can imagine it, we can manufacture it. Core Automation's assists you in developing the right equipment and enclosures for your applications.

# Single-Metered Pedestals



## PRODUCT DESCRIPTION

Core Automation's single-meter underground service distribution and control pedestals, manufactured by Core Automation, Inc., are used for a wide variety of municipal applications. The Single Meter profile pedestal provides power distribution and metering rated for 120 to 480 volts; single phase or three phase applications; 1, 2 or 3 pole main breakers; and may be rated at 100 amp or 200 amp. Core Automation Pedestals are constructed of the highest grade materials using galvanized steel. Our powder coatings will withstand the testing applied to outdoor enclosures and meet or exceed your specifications.

## PRODUCT DETAILS

### STANDARD FEATURES

- 0.075" galvanized steel
- White powder coating, inside & out (custom colors are available)
- Doors open 180°
- Lockable black quarter turn latches
- Vented top hood with bug screen
- Custom sizes available
- Oil resistant gasket
- Top mounted ventilation fans
- Provisions for sub panels
- Concealed hinges
- Integrated solar shields on top
- Optional solar shields on sides and front

### APPLICATIONS

- Athletic field/stadium lighting
- CATV termination
- Cellular
- Wastewater lift stations
- Landscape irrigation
- Parking lot lighting
- Residential applications
- Sign lighting
- Street lighting
- Flood control lift stations
- Tennis court lighting & control

### INDUSTRY STANDARDS

- NEMA Type 3R
- UL Listed Type 3R
- CSA Type 3R
- IEC 60529
- IP 32

**\*MEETS ALL UL508A STANDARDS**