



## PRODUCTS

Core Automation Incorporated's fully-equipped manufacturing facility is qualified and capable of fabricating, assembling, wiring and testing electrical and control systems equipment. Core Automation, Inc. provides fabrication and design services for most hardware and software vendors, which allows us to integrate and support a full complement of hardware and software solutions for *your* control system. If you can imagine it, we can manufacture it. Core Automation's assists you in developing the right equipment and enclosures for your applications.

# Unmetered Pedestals



## PRODUCT DESCRIPTION

Core Automation's unmetered pedestals allow for a variety of applications. Our unmetered pedestals are constructed using galvanized steel and a white powder coating both inside and out. The use of these materials creates an enclosure that excels in both quality and durability. Core pedestals contain lockable, black quarter turn latches, provisions for sub-panels, concealed hinges, and mounting channels for optional mounting of components. Unmetered pedestals fabricated by Core can be used for a wide range of applications such as cellular systems, lighting controls, and locations that specialize in water pumping.

## PRODUCT DETAILS

### STANDARD FEATURES

- 0.075" galvanized steel
- White powder coating, inside & out (custom colors are available)
- Doors open 180°
- Lockable black quarter turn latches
- Vented top hood with bug screen
- Custom sizes available
- Oil resistant gasket
- Top mounted ventilation fans
- Provisions for sub panels
- Concealed hinges
- Integrated solar shields on top
- Optional solar shields on sides and front

### APPLICATIONS

- Athletic field/stadium lighting
- CATV termination
- Cellular
- Wastewater lift stations
- Landscape irrigation
- Parking lot lighting
- Residential applications
- Sign lighting
- Street lighting
- Flood control lift stations
- Tennis court lighting & control

### INDUSTRY STANDARDS

- NEMA Type 3R
- UL Listed Type 3R
- CSA Type 3R
- IEC 60529
- IP 32

**\*MEETS ALL UL508A STANDARDS**